💱 Vaide

USER MANUAL Scrapper subcompact flashlight

CONTENTS

| KEY FEATURES | 3 |
|------------------------|---|
| QUICK START & DIAGRAM | 4 |
| SPECIFICATION | 5 |
| DELIVERY SETS | 5 |
| MOUNTING & MAINTENANCE | 6 |
| CHARGING | 7 |
| STORAGE & WARNING | 8 |
| WARRANTY | 9 |




KEY FEATURES

- 1. Tactical low profile subcompact flashlight
- 2. Lightweight and aluminum structure design
- 3. Click button switch for power on/off
- 4. Constant high, medium, low & strobe mode
- 5. Glove-friendly smart-sense momentary on/off switch for silent and quick operation
- 6. Built-in rechargeable lithium battery compatible with magnetic type charger
- 7. Charging and battery power indicator to clarify the device status



QUICK START & DIAGRAM



· Simply click the On/Off switch to turn the flashlight on or off.

. Double-click the On/Off switch will change to strobe mode. Double click again will resume to constant mode.

. The flashlight has three modes: high, medium, and low.

. When the flashlight is constant on, press the On/Off switch for 1 second to another working mode. Or, when the flashlight is on, hold the on/off switch to change and choose the working mode.

. When the flashlight is on, put a finger over the smart-sensor switch which is on the other side of the unit to momentarily turn off the unit. Move the finger away to resume the unit.

. Power saving: If the flashlight is on at high 500 lumens working mode for more than 1 min, the mode will switch to low working mode.

SPECIFICATION

| LED Lumen | High | Medium | Low |
|---------------------|-------------------------------------|------------|-----------|
| | 500 Lumens | 200 Lumens | 40 Lumens |
| Housing material | Aluminum alloy 6061-T6 | | |
| Dimension | ≤51x28x33mm (2.0x1.1x1.3in) | | |
| Net Weight | ≤55g (1.9oz) | | |
| Battery Type | Build-in rechargeable lithium | | |
| Battery Runtime | 10 Min | 35 Min | 4.5 Hours |
| Working Mode | Constant high, medium, low & strobe | | |
| Working Temperature | -20 to 45°C (-4 to 113°F) | | |



DELIVERY SETS



V Led Light V Magnetic cable V Wrench, 2 Pcs Anti-Retreat Insertions V User Manual V Packing Box



MOUNTING

The flashlight is installed on the gun by means of its integrated weaver mount. Loosen the locking screw, choose proper retreat insertion, put the flashlight onto the weaver or picatinny rail. Choose the proper mounting position and make sure it sits flat on the rail. Align the retreat insertion within the recoil groove on the weaver or picatinny rail, fasten the locking screw. Don't exceed 16 inches/pounds of torque on the flashlight's screws.

SEALED AND WATER-RESISTANT

The unit has an O-ring to prevent the entry of dust or moisture or rain.

MAINTENANCE

Your flashlight, though amazingly tough, is a precision instrument that deserves reasonable cautious care.

When cleaning the flashlight, first blow away any dirt and dust, or use a soft lens brush. Fingerprints and lubricants can


be wiped off with a tissue, or soft clean cotton cloth, moistened with lens cleaning fluid.

All moving parts of the flashlight are permanently lubricated. Do not try to lubricate them.

No maintenance is needed on the light's outer surface, except to occasionally wipe off dirt or fingerprints with a soft cloth.

CHARGING

To charge the flashlight, first turn it off. Plug the charging cable and connect to a USB power adaptor. The magnetic round plate port on the flashlight accepts the magnetic charger head from the charging cable. The charging indicating LED on the flashlight shall be on to ensure that the battery is being charged.



Caution: Keep the port and charger head contact clean at all times. Poor contact

can cause malfunction. Fully charge your flashlight before first use, which may take around 3-4 hours according to the charging condition.

The charging indicator is shown in RED, YELLOW, or GREEN.

| Light Indicating | Red | Yellow | Green |
|-----------------------------|---------------|------------|---------------|
| Battery Capacity Indication | Less than 25% | 25% to 75% | More than 75% |

STORAGE

Avoid storing the flashlight in hot places, such as the passenger compartments of vehicles on hot days. The high

temperatures could adversely affect the lubricants and sealants. A vehicle's trunk, a gun cabinet, or a closet is preferable.

For more information please visit our website: www.vaide.com

SAFETY & WARNING

- · Direct viewing of the flashlight is hazardous to the eyes.
- · Never look directly into the flashlight beam.
- Never point a flashlight at the person.
- . Do not allow children to use flashlights unless under adult supervision.



FIVE YEARS LIMITED WARRANTY

Your Vaide product is warranted free of defects in materials and workmanship for a period of 5 years from the time of purchase by the original purchaser. This warranty covers accidental damage, as well as any defects in materials and workmanship. Batteries, damages caused by misuse or improper handling are not covered. In the event of a defect under this warranty, we promise to repair or replace your product and ship it back to you absolutely free of charge. Also, this warranty is null and void if modification or maintenance is provided by someone other than Vaide. This warranty is non-transferable.

For products not directly purchased from us, please contact the local dealer for an applicable warranty.

For more details please visit our website, thanks for your support.

WWW.VAIDE.COM



| NOTES | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| NOTES | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |

SMALL BODY, GREAT POWER



WWW.VAIDE.COM